

WJ1010-10.0

螺钉式PCB接线端子

下载日期:2024-05-02



	固定式连接器 额定电流: 30 A 额定电压: 300 V 使用线径: 26-10AWG 间距: 10.0 mm
--	---

	目录仅供参考，实际规格依产品工程图为准 版本1.0
--	---------------------------

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	30	-	10
接线范围 Wire Range [AWG]	26~10		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	250	400	630
额定电流 Rated Current [A]	32	32	32
额定冲击电压 Impulse withstand voltage [KV]	6	6	6
导线截面积[硬/柔] Conductor cross section [mm²]	0.5~4.0		

材料 Material

绝缘材料 Insulation Material	PA66
--------------------------	------

WJ1010-10.0

螺钉式PCB接线端子

下载日期:2024-05-02



阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	10.0/1~24
剥线长度 Stripping Length [mm]	4.5~5
螺丝/扭矩 Screw/Torque(Max)[N.m]	M4/1.2
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	260°C/5S
引针尺寸 Pin dimensions [mm]	/
PCB板孔径 PCB Hole Diameter [mm]	/

尺寸图

