

WJ46A

栅栏式接线端子

下载日期:2024-05-02



目录仅供参考，实际规格依产品工程图为准 版本1.0

材质及电镀 Material

螺丝 Screws	M4.0 Steel Ni plated
焊脚 Pin Header	Copper alloy , Sn plated
塑件 Housing	PA66 , UL94V-0

电气性能 Electrical

参考标准 Standard	UL	IEC
额定电压 Rated voltage	300V	400V
额定电流 Rated current	20A	24A
使用线径 Wire range	22-12AWG	2.5mm ²
接触电阻 Contact Resistance	20mΩ	
绝缘电阻 Insulation resistance	500MΩ/DC500V	
耐电压 Withstanding voltage	AC2000V/1Min	
温度范围 Temp.range	-40℃~+105℃	
扭矩 Torque	12.24Kgf.cm/1.2Nm/10.6Lb.in	

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	9.5/2-20
----------------------------	----------

WJ46A
栅栏式接线端子

下载日期:2024-05-02



工作温度 Operating temperature [°C]	-40°C~+105°C
扭矩 Torque	12.24Kgf.cm/1.2Nm/10.6Lb.in

尺寸图

PCB开孔图

